

## Submersible Drainage Pump

Compact designed, suitable for clean water.

- Equipped with mechanical seal and oil seal.
- Overload protection in motor.
- Come with 5 meter plug-in cable.



Model	Dia.	Power	Flow rate	Head
LP120	1"(25 mm)	120W , 220/50Hz	75 L/min	6 M

## Self – Priming Deep Well Pump

Two-line jet pump, available with manual and automatic function.

- Cast iron pump casing.
- Brass impeller, suitable for clean water with suction depth at 15 – 50 meter.
- Overload protection in motor.
- Come with 1.2 meter plug-in cable.



Model	Dia.	Power	Flow rate	Head
LD/ALD11-25	1.25"X1"X1"	1HP , 750W , 220V/50Hz	50 L/min	30 M

## Automatic Pump Control

### Features

Function as a smart sensor which automatically operate the pump by detecting the water when flow through the switch. The pump will automatically shut-off within 7-8 second when user manually stop operating the pump or the sensor detected no water in the system. In case of dry running, the indicator light will be shown on the dial to inform the user. When the water is fill back in the system, the user must press the "Reset" button to restart the function back to its normal stage.



Power	220V/50Hz
Power current	≤ 10 amps
Pump power	≤ 1.1 kw(1.5HP)
Design pressure	≤ 100 m (10Kg/Cm <sup>2</sup> )
Diameter	1" x 1"
Liquid temperature	≤ 60 °C